



# TECHNICAL INFORMATION SHEET

## DEFOM<sup>®</sup> E 50 79 – 4

### TYPE:

READY TO USE HIGH SOLID POLISH FOR  
**MATALL SURFACES** FREE OF ANY KIND OF  
CHLORINATED SOLVENTS OR CFC`S.

**MATERIAL PRESSURE** : 0,3 Bar.

### BASE:

SOLUTION OF ACTIVE SUBSTANCES IN PETROLEUM  
DESTILLATES.

### APPLICATION:

CONCENTRATES ARE READY TO USE POLISH.  
THE CONCENTRATION OF ACTIVE

### DESCRIPTION:

DEFOM<sup>®</sup> E5079-4 ACTS AS A POLISH AND FOR:

#### ♦ METALL PARTS AND SURFACES

### PERFORMANCE:

- ♦ SPAYABLE.
- ♦ UNIVERSAL TYPE FOR ALL METALL SURFACES.
- ♦ COLD APPLIABLE.
- ♦ LOW USAGE.
- ♦ FASTER DRAYING TIME.
- ♦ ADJUSTED VISCOSITY, POSSIBLE FOR BRUSHING.

SUBSTANCES ARE EXTREMELY HIGHER IN  
COMPARISON TO CONVENTIONAL POLISHING  
AGENTS. FOR THIS REASON THE  
CONCENTRATES MUST BE SPRAYED VERY  
CAREFULLY IN ORDER TO ACHIEVE A THIN  
LAYER WITH UNIFORM DISTRIBUTION.  
THICKER LAYER OF POLISH AGENTS WILL NOT  
ENHANCE THE MATTNES EFFECT BUT RATHER  
THE OPPOSITE. FOR THE APPLICATION OF  
CONCENTRATES WE RECOMMEND TWO  
SEPARATE PRESSURES. ADJUSTMENTS: ONE FOR  
THE AIR PRESSURE ON THE METALL SURFACE  
FOR ATOMIZATION AND ONE FOR THE  
PRESSURE ON MATERIAL

AT LOW METALL TEMPERATURES, WE  
RECOMMEND A BLOW OUT WITH AIR OR A WIPE  
WITH CLOTH AFTER APPLYING.

### PHYSICAL PROPERTIES:

DENSITY 20°C : 0,76 ± 0,02 G/CM<sup>3</sup>.  
APPEARANCE : WHITE, LIQUID.  
FLASH POINT : > 27° C.

CUSTOMS No.: 34.05.90.10

### DEVICES:

BRUSH, AIRLESS

**STIR WELL PRIOR TO USE!**

### STORAGE:

DO NOT STORE THIS POLISH OUTSIDE. STORAGE TEMPERATURE : 5 - 35°C. KEEP AWAY FROM IGNITION SOURCES  
AND PROVIDE FOR GOOD VENTILATION. SHELF LIFE: 9 MONTHS IF STORED IN TIGHTLY CLOSED CONTAINER.

### **Preliminary tests are recommended**

The information contained herein are offered free of charge for use by technically qualified personnel at their discretion and risk. All  
statements, technical information and recommendation contained herein are based on tests and data which we believe to be reliable, but  
the accuracy or completeness thereof is not guaranteed and no warranty of any kind is made with respect thereto